

1.2M KU-BAND

RX/TX

SERIES

1134



Prodelin Corporation is the world's largest manufacturer of Rx/Tx VSAT antennas. We have the broadest product line in the industry including Receive Only, Rx/Tx and Rural Telephony antenna systems. Prodelin offers nineteen antenna sizes, 47cm to 4.5M. Prodelin is the leader in obtaining type certifications and approvals for Intelsat, AsiaSat and Eutelsat. Prodelin antennas provide the best quality in the market due to the sophisticated, precision SMC compression molding process technology. Prodelin provides the best value antenna solution to the market with competitive prices, the highest quality products and superb engineering support. Prodelin is ISO registered, KEMA # 70022.01. **Prodelin - The Market Leader in VSAT Antennas.**

Back View
1.2M Rx/TxOption
Feed Horn w/ OMT &
Transmit Reject Filter

Key Features

- IntelSat approval number IAO45A00
- AsiaSat approved
- Eutelsat VSAT type approval
- ETSI Certification
- New optics for low cross-pol compliance
- Precision compression molded offset reflector
- Low cost shipping & easy local handling
- Simplified one-man installation - less than one hour assembly

Receive/Transmit

Series 1134

1.2M KU-BAND
RX/TX
SERIES
1134

Electrical		Series 1134 Ku-Band
Antenna Size		1.2 M (47 in.)
Operating Frequency (GHz)	Receive Transmit	10.95 - 12.75 GHz 13.75 - 14.5 GHz
Midband Gain (+ .2dB)	Receive Transmit	41.5 dBi 43.0 dBi
Antenna Noise Temperature		
20° elevation		46 K
30° elevation		43 K
Sidelobe Envelope, Co-Pol (dBi)		
1° < θ < 20°		29-25 Log θ dBi
20° < θ < 26.3°		-3.5 dBi
26.3° < θ < 48°		32-25 Log θ dBi
48° < θ		-10 dBi (averaged)
Cross-Polarization	Within 1 dB contour Any Angle off Axis	-30 dB Max. -25 dB Max.
VSWR		1.3:1 Max.
Mechanical		
Reflector Material	Glass Fiber Reinforced Polyester SMC	
Antenna Optics	Prime Focus, Offset Feed	
Mast Pipe Size	5" SCH 40 Pipe (2.88" OD) 73.2 mm.	
Elevation Adjustment Range	5° to 90° Continuous Fine Adjustment	
Azimuth Adjustment Range	+ 20° Fine, 360° Continuous	
Mount Type	Elevation over Azimuth	
Shipping Specifications	90 lbs. (41 kg.)	
Environmental Performance		
Wind Loading	Operational Survival	50 mph (80 km/h) 125 mph (201 km/h)
Temperature	Operational Survival	-40° to 140° F (-40° to 60° C) -50° to 160° F (-46° to 71° C)
Rain	Operational Survival	1/2" /hr 2" /hr
Ice	Operational Survival	----- 1/2" radial
Atmospheric Conditions	Salt, Pollutants and Contaminants as Encountered in Coastal and Industrial Areas	
Solar Radiation	360 BTU/h/ft ²	



1700 NE Cable Drive • Conover, NC 28613 USA
Tel: (828) 464-4141 • Fax: (828) 466-0860
www.prodelin.com

© Copyright 2000 Prodelin, a TriPoint Global Company.
All product specifications subject to change without notice.
The Prodelin logo is a trademark of TriPoint Global.